



**WACKER
NEUSON**
all it takes!

EZ26-2

Tracked Zero Tail Excavator



Powerful all-rounder

The EZ26 guarantees flexibility and user-friendliness with high performance features. The low weight allows transport, including of attachments, by car trailer. The wide field of vision around the machine from the cab increases the safety of the operator and the construction site environment. It also ensures constant control of the working environment. The simultaneously high performance and high operating comfort thanks to the wide access, jog-dial operating system and clear machine display make the EZ26 a feel-good zone for the operator.



Air conditioning system

Ensures a pleasant and constant temperature at the workplace. This can be individually adjusted manually with the fan.



Optimal maintenance access

The high productivity of our excavators is not just due to the durable technology. Most service work can be completed in a short time due to quick and easily accessible maintenance points.



Large comfort cabin

The ergonomically optimised comfort cab offer 360° visibility, plenty of legroom and headroom and a wide entry. This promotes a high level of safety and flexibility in the work space, adjusted to the individual needs of the operator.



Zero Tail

When space is limited: Pivot safely, even in the tightest of spaces or right next to the wall.

Optimal working in limited working conditions, high manoeuvrability and time savings are guaranteed.



2 lifting points on the roof

The machine can be moved on the construction site easily without problems using a crane. Also, loading and unloading the excavator from the truck can be done quickly.



Hydraulic joystick operation

The ergonomic and sturdy joysticks, which work completely proportionally, expand the functions and possibilities for controlling the excavator. The operator can carry out movements more precisely and work with increased concentration.

Technical Information

	Units	EZ26-2
Hydraulic		
Operating pressure	bar	240
Mechanical – Output Details		
Nominal engine speed	1/min	2,350
Travel speed	km/h	4.3
Mechanical Details		
Length	mm	4,199
Width	mm	1,550
Height	mm	2,412
Operating weight (min.-max.)	kg	2,455 - 3,358
Digging depth (max.)	mm	2,803
Engine		
Cooling		Water-cooling
Engine type		Diesel engine
Cylinder capacity	cm ³	1,266
Inclined position max.	°	30
Tank capacity	l	40

	Units	EZ26-2
Oil filling max.	l	4.4
Effective power	KW	14.6
Nominal engine speed	1/min	2,350
Starter battery voltage	V	12
Manufacturer		Yanmar
Engine designation		3TNV80F-NPWN
Environmental Data		
Sound power LWA, guaranteed	dB(A)	93
Sound power LWA (Standard)		2000/14/EG
Operating Fluids		
Oil volume	l	26,100
Cooling fluid volume	l	5.4
Hydraulic fluid volume	l	34.5
Chassis		
Drive unit		axial piston motor
Shipping and Storage		
Shipping weight	kg	2,480 - 2,700

