



## DPU110rLem870

### Remote-control vibratory plate

#### Powerful compaction

Sturdy and compact in design, the remote-controlled vibratory plates offer the same high compaction performance as the models with center pole. The convenient remote control with two joysticks allows the operator to work away from vibrations, exhaust emissions and noise pollution. The innovative control unit simultaneously controls forward travel and rotational movement allowing the plate to be steered efficiently and precisely even on curves and around obstacles.

## Highlights

- Compact dimensions, high performance
- Sturdy and durable
- Infra-red remote control with tried and tested safety features
- Variable, precise control

## Technical Data

### ■ Mechanical - Output Details

Centrifugal force	110 kN
Area capacity	1,462.0 m <sup>2</sup> /h
Forward Running	28.0 m/min
Gradeability	32.0 %
Vibrations (Hz)	60.0 Hz

### ■ Mechanical Details

Length Baseplate	1,182.0 mm
Width	870.0 mm
Width Baseplate	870.0 mm

Height	833.0 mm
Height Cover frame	822.0 mm
Thickness Baseplate	14.0 mm
Operating weight	793.0 kg
Ground clearance	830.0 mm

### ■ Engine

Effective power	16.0 KW
Nominal Engine speed	2,700.0 1/min

### ■ Electrical System

Remote Control Range	20.0 m
----------------------	--------