



RD18-100c

Tandem roller

Compact and maneuverable

The RD18 is a compact and particularly maneuverable roller in the 1,8-t class. The 3-point articulated joint, combined with a large drum diameter, delivers even compaction performance and a high-quality asphalt surface. The user benefits from a comfortable work platform and intuitive operation. A feature of the RD18 is the one-sided drum lifting point with drums offset, which makes precise compaction possible very close to edges and walls on both sides.

Highlights

- Combination roller: Rear axle with rubber tires
- Ergonomic work platform
- One-sided drum fastening with drum offset
- Uniform operating concept
- Large line-of-sight, compact construction

Technical Data

■ Mechanical - Output Details

Gradeability	30.0 %
Gradeability max. (without vibration)	40.0 %
Travel speed	0.0 - 11.0 km/h
Static linear load (front)	0.81 kg/mm
Compaction force Level I (front)	29 kN
Compaction force Level II (front)	22 kN
Vibration frequency Level I (front)	61.0 Hz
Vibration frequency Level II (front)	48.0 Hz
Amplitude Level I (front)	0.3800 mm
Amplitude Level II (front)	0.3800 mm
Centrifugal force Level I (front)	17 kN

■ Mechanical Details

Length	2,309.0 mm
Width	1,040.0 mm
Operating weight	1,640.0 kg
Dry Weight	1,500.0 kg
Gross vehicular weight	1,690.0 kg
Operating width	1,040.0 mm
Ground clearance Middle	240.0 mm
Turning radius inside	2,130.0 mm

Operating weight with roll-over protective structure	1,640.0 kg
Wheelbase	1,560.0 mm
Operating weight, max.	1,740.00 kg
Empty weight with ROPS	1,500.0 kg
Turning radius outside	3,165.0 mm

■ Engine

Cylinder capacity	1,123.0 cm ³
Effective power	16.3 KW
Nominal Engine speed	2,600.0 1/min
Standard (Effective power)	ISO 14396
Starter battery Voltage	12.0 V
Battery capacity (nom. value)	70.0 Ah
Engine Manufacturer	Kubota
Engine Designation	D1105-E4B

■ Environment Data

Sound level LpA	84.0 dB(A)
Sound power LWA, measured	103.0 dB(A)
Sound power LWA, guaranteed	104.0 dB(A)
Exhaust aftertreatment	no
Catalyst	no
Particle filter	no

CO2 (NRSC)	1,018.0 g/KWh
------------	---------------

■ Operating Fluids

Water tank capacity	70.0 l
---------------------	--------

Fuel Tank capacity	33.0 l
--------------------	--------

■ Chassis

Pendulum angle +/-	8.0 °
--------------------	-------

Width over tires (rear)	1,000.0 mm
-------------------------	------------

Number of tires (rear)	4.0
------------------------	-----

Wheel size (rear)	205/60-R16
-------------------	------------

Wheel load per tire (rear)	208.8 kg
----------------------------	----------